ELCO Lighting

Project Name:
Fixture Type:
Date:

6″ E26 MEDIUM BASE SLOPED CEILING

75W-150W, 120V, Medium Base E26 Socket



THE SLANT™ SYSTEM

ELCO Slant allows for installation in sloped ceilings ranging from 2/12 (10°) to 6/12 (30°).

FEATURES

- Built-in thermal protector to guard against improper lamping, enhancing safety during operation.
- Designed to fit in 2″ x 8″ joist construction.
- IC and Non-IC New Construction housings.
- Sloped ceilings 2/12 (10°) to 6/12 (30°).

SET UP

1. Select a New Construction or Remodel Housing.

2. Select a Trim.
(Lamp required, sold separately. Refer to trim listing for compatible lamp.)



SPECIFICATIONS

Wattage	75W MAX - 150W MAX
Voltage	120V
Lamp Type	75W MAX PAR30, 150W MAX PAR38
Socket	Medium Base E26
Damp Location	cUL Listed
Sloped Pitch Range	10° 2/12 · 14° 3/12 · 18.5° 4/12 · 22.5° 5/12 · 30° 6/12
Finishes	White · Black · Bronze · Black/ White · Clear/ White

2042 E. Vernon Ave., Vernon, CA 90058 • Tel (323) 231-2600 Fax (323) 231-3200 • elcolighting.com
© ELCO Lighting 2025. All rights reserved • Rev. 30 April 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

STEP 1. Specify Housing part number (Select one) Example: EL936ICA

6″ LINE VOLTAGE SLOPED CEILING IC HOUSINGS

ITEM	WATTAGE	APPLICATION	SPECIFICATION/VOLTAGE
EL			
EL	**936** 90W MAX **918** 75W MAX	**(Blank)** New Construction **R**[1] Remodel	**ICA** IC Airtight, 120V
		[1]Only for 75W Housing	

6″ LINE VOLTAGE SLOPED CEILING NON-IC HOUSINGS

ITEM	WATTAGE	APPLICATION	SPECIFICATION/VOLTAGE
EL			
EL	**900** 150W MAX	**H** New Construction **R** Remodel	**T** Non-IC, 120V

STEP 2. Specify Trim part number (Select one)

6″ LINE VOLTAGE SLOPED TRIMS



Style: **Shower Trim with Albalite Lens**
Item: **EL12W** (All White)
EL12B (All Black)
EL12BZ (All Bronze)
Lamp: 60W A19



Style: **Fresnel Shower**
Item: **EL13W** (All White)
EL13B (All Black)
Lamp: 60W A19



Style: **Adjustable Baffle with Reflector**
Item: **EL601W** (All White)
EL601B (Black/White Ring)
Lamp: 75W PAR30



Style: **Baffle with PAR30 Gimbal**
Item: **EL614W** (All White)
EL614B (All Black)
EL614C (Clear/White Ring)
Lamp: 75W PAR30




Style: **Baffle with PAR38 Gimbal**
Item: **EL615W** (All White)
EL615B (All Black)
EL615C (Clear/White Ring)
Lamp: 150W PAR38



Style: **Reflector**
Item: **EL616W** (All White)
Lamp: 75W PAR30, 150W PAR38



Style: **Reflector with Coil Springs**
Item: **EL617W** (All White)
Lamp: 42W 4-Pin CFL, 150W PAR38



Style: **Baffle with Coil Springs**
Item: **EL622W** (All White)
EL622B (Black/White Ring)
Lamp: 150W PAR38



Style: **Adjustable Baffle with Bracket**
Item: **EL622KW** (All White)
EL622KBB (All Black)
EL622KBZ (Bronze)
EL622KB (Black/White Ring)
Lamp: 75W PAR30, 150W PAR38

© ELCO Lighting 2025. All rights reserved • Rev. 30 April 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

STEP 2. Specify Trim part number (Select one)

6″ LINE VOLTAGE SLOPED TRIMS



Style: **Baffle with Coil Springs**
Item: **EL623W** (All White)
Lamp: 42W 4-Pin CFL, 150W PAR38



Style: **Adjustable Baffle with Gimbal**
Item: **EL624W** (All White)
Lamp: 75W PAR30 or LED





Style: **Adjustable Baffle with Gimbal**
Item: **EL626W** (All White)
EL626B (Black/White Ring)
Lamp: 150W PAR38 or LED

PRODUCT DIMENSIONS


LINE VOLTAGE IC SLOPED HOUSINGS

EL936ICA
MEDIUM BASE IC AIRTIGHT DOUBLE WALL NEW CONSTRUCTION






EL918ICA
MEDIUM BASE IC AIRTIGHT SINGLE WALL NEW CONSTRUCTION





EL918RICA
MEDIUM BASE IC AIRTIGHT REMODEL HOUSING






© ELCO Lighting 2025. All rights reserved • Rev. 30 April 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT DIMENSIONS


LINE VOLTAGE NON-IC SLOPED HOUSINGS

EL900HT
MEDIUM BASE NON-IC NEW CONSTRUCTION





EL900RT
MEDIUM BASE NON-IC REMODEL






PRODUCT DIMENSIONS

6″ SLANT™ SLOPED TRIMS

EL12 - 6″ SHOWER TRIM WITH ALBALITE LENS







W (All White)




B (All Black)



BZ (All Bronze)

EL13 - 6″ SHOWER TRIM WITH FRESNEL LENS








W (All White)



B (All Black)

EL601 - 6″ ADJUSTABLE BAFFLE WITH REFLECTOR








W (All White)



B (Black/White)

EL614 - 6″ BAFFLE WITH PAR30 GIMBAL





W (All White)



B (All Black)




C (Clear/White)

© ELCO Lighting 2025. All rights reserved • Rev. 30 April 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT DIMENSIONS

6″ SLANT™ SLOPED TRIMS

EL615 - 6″ BAFFLE WITH PAR38 GIMBAL





W (All White)




B (All Black)



C (Clear/White)


EL616 - 6″ REFLECTOR





W (All White)

EL617 - 6″ REFLECTOR WITH COIL SPRINGS









W (All White)

EL622 - 6″ BAFFLE WITH COIL SPRINGS









W (All White)



B (Black/White)

EL622K - 6″ ADJUSTABLE BAFFLE TRIM WITH BRACKET







W (All White)



BB (All Black)




BZ (All Bronze)



B (Black/White)

EL623 - 6″ BAFFLE WITH COIL SPRINGS








W (All White)

© ELCO Lighting 2025. All rights reserved • Rev. 30 April 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT DIMENSIONS

6″ SLANT™ SLOPED TRIMS

EL624 - 6″ ADJUSTABLE BAFFLE WITH GIMBAL








W (All White)

EL626 - 6″ ADJUSTABLE BAFFLE WITH GIMBAL








W (All White)



B (Black/White)

EL642 - 6″ REFLECTOR WITH ALBALITE LENS







B (Black/White)

© ELCO Lighting 2025. All rights reserved • Rev. 30 April 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.

TECHNICAL DETAILS FOR IC HOUSINGS

Construction: Airtight aluminum construction, available in single or double wall configurations. Rated for direct contact with insulation. Adjustable to fit ceiling thicknesses up to 1 ¼".

Installation: Designed for ceiling plenums with 2x8 joists or taller. High-strength hanger bars can be nailed to joists and are adjustable up to 24", with repositioning up to 90°. Suitable for T-grid and drop ceiling applications.

Junction Box: Accommodates straight conduit runs with seven ½" trade size conduit knockouts and four pry-out knockout slots for easy Romex installation.

Hanger Bars: Pre-installed with True Nail for easy installation in various lumber types, featuring integral T-bar slots and leveling flanges for single-person installation.

Listings: cUL Listed for Damp Location, Direct Contact with Insulation and Combustible Material, and Feed Through, and meets restricted air flow requirements per ASTM E-283 Standard.

TECHNICAL DETAILS FOR NON-IC HOUSINGS

Construction: Non-IC housing designed for installation where insulation is kept at least 3 inches away from the fixture. Available in single-wall construction. Adjustable for ceiling thicknesses up to 1 ¼".

Housing Compatibility: Fits in 2" x 8" joist constructions.

Installation: Designed for new construction or remodel applications.

Hanger Bars: Adjustable up to 24", can be repositioned 90°, and have T-bar slots for easy installation in grid ceilings. Includes bar hangers with True Nail for quick attachment to joists.

Junction Box: Seven ½" conduit knockouts for conduit runs. Four pry-out knockouts for Romex wiring.

Listings: cUL Listed for Damp Location and Feed Through, and meets restricted airflow requirements per ASTM E-283 Standard.

© ELCO Lighting 2025. All rights reserved • Rev. 30 April 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.