ELCO Lighting

The Best Choice in Lighting



4″ & 6″ High-End Residential & Light Commercial IC & Non-IC Recessed Lighting







Introducing The Cedar System



ELCO Lighting Cedar System was designed as a high output LED downlight for High-End Residential and Light commercial applications for IC and Non-IC conditions. This architectural grade downlight system is offered in apertures of 4″ to 6″ in baffle, reflector, wall wash, adjustable and square. The Cedar System ranges from 2700K to 5000K for 850 lumens to 2000 lumens.




90+ CRI | INSULATED CEILING | WET LOCATION | TITLE 24 COMPLIANT | LED | AIRTIGHT

2042 East Vernon Avenue
Vernon, CA 90058
Tel. 323.231.2600
www.elcolighting.com

4” Housing with **Driver 850 and 1250 Lumen IC and Non-IC**

IC 1250 lm



IC 850 lm
Non IC 850-1250 lm



IC 850 lm
Non IC 850-1250 lm



4” Frame	Construction	Color Const.	Voltage	Lumen	IC Airtight	Dimming	Optional
E4L							
	(blank) New **R** Remodel	**C** TrueWhite™ **M** 3 MacAdam	**1** 120V **2** 277V **U** 120/277V (0-10V only)	**08** 850 lm **12** 1250 lm	**(blank)** Non-IC **ICA** IC Airtight	**(blank)** Triac/ELV **D** 0-10V **S** Sunset	**EM1** Emergency Backup up to 700 lm output **EM2** Emergency Backup up to 1100 lm output

4” Light **Engine 850 and 1250 lumen**

Round Baffle (H)



Round Reflector (W)



Round Wall Wash (W)



Square on Square Baffle (BZ)



Square on Round Baffle (B)



Square on Round Reflector (H)



4” Light Engine	Style	Color Const.	Lumen	Color Temp.	Trim Finish*
E4					
	14 Round Baffle **10** Round Reflector **11** Round Wall Wash **15** Square on Square Baffle **24** Square on Round Baffle **20** Square on Round Reflector	**C** TrueWhite™ **M** 3 MacAdam	**08** 850 lm **12** 1250 lm	**27** 2700K **30** 3000K **35** 3500K **40** 4000K **50** 5000K **SD** Sunset	**W** All White **BZ** All Bronze **H** Haze w/White Ring **N** All Nickel **B** Black w/White Ring **CP** All Copper

6” Housing with **Driver 850, 1250 and 2000 Lumen IC and Non-IC**

6” Frame	Construction	Color Const.	Voltage	Lumen	IC Airtight	Dimming	Optional
E6L							
	(blank) New **R** Remodel	**C** TrueWhite™ **M** 3 MacAdam	**1** 120V **2** 277V **U** 120/277V (0-10V only)	**08** 850 lm **12** 1250 lm **20** 2000 lm	**(blank)** Non-IC **ICA** IC Airtight	**(blank)** Triac/ELV **D** 0-10V **S** Sunset	**EM1** Emergency Backup up to 700 lm output **EM2** Emergency Backup up to 1100 lm output

6” Light **Engine**
850, 1250 and 2000 lumen

Round Baffle (BZ)



Round Reflector (C)



Baffle Adjustable (W)



6” Light Engine	Style	Color Const.	Lumen	Color Temp.	Trim Finish*
E6					
	14 Round Baffle **10** Round Reflector **16** Baffle Adjustable **17** Reflector Adjustable	**C** TrueWhite™ **M** 3 MacAdam	**08** 850 lm **12** 1250 lm **20** 2000 lm	**27** 2700K **30** 3000K **35** 3500K **40** 4000K **50** 5000K **SD** Sunset	**W** All White **BZ** All Bronze **H** Haze w/White Ring **B** Black w/White Ring **C** Chrome w/White Ring

*NOT ALL TRIM STYLES ARE AVAILABLE IN ALL TRIM FINISHES

2042 East Vernon Avenue Vernon, CA 90058 • Tel. 323.231.2600 • www.elcolighting.com