ELCO Lighting

Project Name:
Fixture Type:
Date:

THE KOTO™ PEEK MULTIPLES

Single, Double & Triple Head, 350–1500 lm per head, 2400K–4000K, CT5, Sunset, Human Centric, Tunable White (DALI-2), 120V & 120-277V



DIRECTIONAL / RECESSED-TO-ADJUSTABLE DOWNLIGHTING SYSTEM

Combines the clean appearance of recessed lighting with the flexibility of adjustable cylinders. Available in single, double, and triple-head configurations, each fixture can remain recessed for a minimalist look or be pulled down, rotated, and aimed exactly where light is needed.

FEATURES

- IC Rated for direct contact with insulation.
- Up to 30° adjustment when recessed; up to 90° tilt and 360° rotation when pulled out.
- Choose the ideal configuration for accent lighting, wall washing, retail displays, or hospitality applications.
- Accommodates ceiling thicknesses ½″ to 1 ½″
- Field-serviceable & upgradable LED module with in-field changeable optics.

SET UP


1. Select a Koto™ Peek Multiples Housing with integrated LED Module (single, double, or triple head).

2. Select a Trim (White, Black, or Spackle Frame Trimless) to match the number of heads.

Peek Multiples



Trim or Trimless Options



SPECIFICATIONS

Lumens/Wattage Per Head	350 lm (5W), 750 lm (10.5W), 850 lm (10.5W/12.5W), 950 lm (10.5W), 1050 lm (12.5W), 1150 lm (12.5W), 1350 lm (12.5W), 1500 lm (14W)
Voltage	120V or 120-277V
Color Temp.	2400K, 2700K, 3000K, 3500K, 4000K, CT5 (2700K–5000K switchable), Sunset, Human Centric, Tunable White (4000K–1800K)
CRI	95+
Damp Location	Listed
Dimming	Triac/ELV 0-10V/Triac/ELV (1%) DALI-2 dims to (0.1%)
Beam Angle	10°, 18°, 25°, 38°, 60° & 90°
Finishes	All White, All Black

2042 E. Vernon Ave., Vernon, CA 90058 • Tel (323) 231-2600 Fax (323) 231-3200 • elcolighting.com
© ELCO Lighting 2026. All rights reserved • RV1 August 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

STEP 1. Specify Koto™ Peek Multiples Housing with Integrated Koto™ Module part number (Select one)

Example: E2PMB2W-0727

ELCO PEEK MULTIPLES	NUMBER OF HEADS	FINISH	LUMENS/WATTAGE PER HEAD	COLOR TEMP	DIMMING/ VOLTAGE	BEAM ANGLE
E2PM						
	A1 1 Head **B2** 2 Heads **C3** 3 Heads	**W** White Housing & Heads **BB** Black Housing & Heads	**120V Triac/ELV**			
			-03[1] 350 lm (5W) **-07** 750 lm (10.5W) **-09** 950 lm (10.5W) **-11** 1150 lm (12.5W) **-13** 1350 lm (12.5W) **-15** 1500 lm (14W)	**24** 2400K **27** 2700K **30** 3000K **35** 3500K **40** 4000K **SD**[2] Sunset **HC**[3] Human Centric	**(Blank)** 120V Triac/ELV	**(Blank)**[4] 38° **-S** 18° **-N** 25° **-W** 60° **-E**[5] 90° **-T**[6] 10°
			-08 850 lm (10.5W) **-10** 1050 lm (12.5W)	**CT5** CCT Switch: 2700K, 3000K, 3500K, 4000K, 5000K		
			[1] Available in 2700K & 3000K	[2] Sunset, Dim to Warm technology, dims from 3000K to 1800K. Available with 950 lm & 1150 lm only. [3] Human Centric, Dim to Warm technology, dims from 4000K to 2200K. Available with 1150 lm only.		[4] 38° installed on module with 25° & 60° included in the box. [5] 90° available with frosted reflector only. [6] 10° available with 2700K & 3000K in 350 lm & 750 lm only
			120V Triac/ELV Focus Beam			
			-07 750 lm (10.5W)	**27** 2700K **30** 3000K **35** 3500K **40** 4000K **SD**[2] Sunset	**(Blank)** 120V Triac/ELV	**-FC**[7] 18° - 50°
				[2] Sunset, Dim to Warm technology, dims from 3000K to 1800K.		[7] Adjustable Focus offers 18° - 50° with a twist of the snoot.
			120-277V Triac/ELV/0-10V			
			-10 1050 lm (12.5W)	**27** 2700K **30** 3000K **35** 3500K **40** 4000K **SD**[2] Sunset	**X** 120-277V, 0-10V, Triac & ELV (Dims to 1%)	**(Blank)**[4] 38° **-S** 18° **-N** 25° **-W** 60° **-E**[5] 90°
				[2] Sunset, Dim to Warm technology, dims from 3000K to 1800K.		[4] 38° installed on module with 25° & 60° included in the box. [5] 90° available with frosted reflector only.
			DALI-2 DT8 Tunable White			
			-08 850 lm (12.5W)	**41** Tunable White 4000K - 1800K	**A** 120-277V DALI 2 Tunable White (Dims to 0.1%)	**(Blank)**[4] 38° **-S** 18° **-N** 25° **-W** 60° **-E**[5] 90°
						[4] 38° installed on module with 25° & 60° included in the box [5] 90° available with frosted reflector only

STEP 2. Specify Koto™ Peek Multiples Trim or Spackle Frame part number (Select one)

Example: E2M2B10W

TRIM & SPACKLE FRAME TRIMLESS

MULTIPLES TRIM	NUMBER OF HEADS	STYLE
E2M		
	1A 1 Head **2B** 2 Heads **3C** 3 Heads	**10W** White Trim **10BB** Black Trim **22SF** Spackle Frame Trimless

© ELCO Lighting 2026. All rights reserved • RV1 August 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

Field Changeable Secondary Module Optics (Not Compatible with Koto™ Focus Module)											
L45 Black Hex Louver	**L57** White Hex Louver	**L46** Linear Lens	**L47** Spread Lens	**L49** Frosted Diffuser	**L51** CCT Reducer	**L52** Blue Color Shifter	**L53** Pink Color Shifter	**L54** Single Asymmetric	**L55** Double Asymmetric	**L50W** White Snoot	**L50B** Black Snoot

Koto™ Modules - Lumen Value Multiplier			
CCT	Multiplier	Beam Angle	Multiplier
2700K	0.96	**18˚**	0.84
3000K	1	**25˚**	0.89
3500K	1.05	**38˚**	1
4000K	1.085	**60˚**	1.065
SD	0.80	**90˚**	0.95
HC	0.85		


PRODUCT DIMENSIONS

KOTO™ PEEK MULTIPLES HOUSING WITH INTEGRATED KOTO™ MODULE


E2PMA1W/BB
SINGLE HEAD IC AIRTIGHT NEW CONSTRUCTION HOUSING



E2PMB2W/BB
DOUBLE HEAD IC AIRTIGHT NEW CONSTRUCTION HOUSING



E2PMC3W/BB
TRIPLE HEAD IC AIRTIGHT NEW CONSTRUCTION HOUSING




© ELCO Lighting 2026. All rights reserved • RV1 August 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT DIMENSIONS

STANDARD KOTO™ MULTIPLES TRIMS

E2M1A10 - SINGLE HEAD TRIM






W (All White)



BB (All Black)

E2M2B10 - DOUBLE HEAD TRIM






W (All White)



BB (All Black)

E2M3C10 - TRIPLE HEAD TRIM






W (All White)



BB (All Black)


STANDARD KOTO™ MULTIPLES TRIMLESS

E2M1A22SF - SINGLE HEAD SPACKLE FRAME






E2M2B22SF - DOUBLE HEAD SPACKLE FRAME





E2M3C22SF - TRIPLE HEAD SPACKLE FRAME







© ELCO Lighting 2026. All rights reserved • RV1 August 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

ACCESSORIES

LENS & OPTICS (field changeable. Not compatible with Focus Module)

FIELD CHANGEABLE LENS		HEX LOUVER	LINEAR LENS	SPREAD LENS
				
EP731C (18°) / **EP732C** (25°) **EP733C** (38°) / **EP734C** (60°)	**EP739C** (90°) Frosted Reflector	**L45** (Black) / **L57** (White) For a better glare shield	**L46** For a wide rectangular illumination pattern	**L47** For a symmetrical broadening of light beams

FROSTED DIFFUSER	COLOR SHIFTERS	SINGLE ASYMMETRIC LENS	DOUBLE ASYMMETRIC LENS	SNOOTS
				
L49 For a softer light	**L51** (Color temp. reducer) **L52** (Blue) / **L53** (Pink)	**L54** For elliptical illumination pattern	**L55** For elliptical illumination pattern	**L50W** (White) / **L50B** (Black) Reduces glare and light spill

© ELCO Lighting 2026. All rights reserved • RV1 August 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

TECHNICAL DETAILS

Design: Patented pull-out design transforms the fixture from a clean recessed appearance to a fully adjustable directional fixture in seconds. Housing adjusts ½″ to 1 ½″ to accommodate varying ceiling thicknesses without removing the housing.

Construction (Light Engine): Diecast aluminum body with heat fins allow for efficient cooling

Installation (Light Engine): Twist-on design for toolless trim installation. For use with standard Koto™ Multiples trims only.

Hanger Bars: Pre-installed hanger bars with True Screw easy installation in regular lumber, engineered lumber, and laminated beams. Integral T-bar slots for easy installation in T-bars. Spans up 24″ and can be repositioned 90º. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while easily aligning the housings with the joists.

LED Technology: Extremely accurate Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixilation.

Electrical: Module connects to 120V or 120-277V power supply depending on module chosen. High efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

Dimming: Works with 120V and 120-277V Triac/ELV type dimmers. Dims down to 5%. 0-10V/Triac/ELV dims down to 1% and DALI-2 dims to 0.1%. For full list of dimmers, refer to the Dimmer Compatibility List. Industry leading dimming that dims smoothly with no hot spots or flickering

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Listings: UL and cUL Listed for Damp Locations. RoHS Compliant. Meets Energy Star & California Title 24 JA8-2025-E standards.

Warranty: ELCO Products are built to last with a 5-year Limited warranty.

© ELCO Lighting 2026. All rights reserved • RV1 August 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

DIMMER COMPATIBILITY CHART

FOR REFERENCE ONLY

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

MANUFACTURER	PRODUCT	PART NUMBER	DIMMED LIGHT OUTPUT RANGE
120V - Triac/ELV Dimmers for ELK10DX			
Lutron	Skylark Contour dimmer, Incandescent/Halogen, 3-way	CT-103P-WH	1% - 100%
	Nova T dimmer, electronic low-voltage (ELV)	SELV-300P-WH	1% - 100%
	Skylark dimmer, Incandescent, single pole	S-600P-WH	1% - 100%
	Skylark Contour dimmer, CFL/LED/Incandescent, 3-way	CTCL-153P-WH	1% - 100%
	Diva dimmer, electronic low-voltage (ELV), 3-way	DVELV-303P-WH	1% - 100%
	Diva dimmer, Incandescent/Halogen, 3-way	DV-600P-WH	1% - 100%
	Diva C.L. dimmer, CFL/LED/Incandescent, 3-way	DVCL-153P-WH	1% - 100%
	Ariadni dimmer, magnetic low-voltage (MLV), 3-way	AYLV-600P-WH	1% - 100%
	Maestro dimmer, electronic low-voltage (ELV)	MAELV-600-WH	1% - 100%
	Maestro C.L. dimmer, CFL/LED/Incandescent, single pole	MACL-153M-WH	1% - 100%
	RadioRA 2 dimmer, for Incandescent, Halogen, and MLV	RRD-PRO-WH	1% - 100%
	RadioRA 2 dimmer, for Incandescent/Halogen/MLV, neutral wire required	RRST-PRO-N-WH	1% - 100%
	Diva C.L. dimmer, CFL/LED/Incandescent, 3-way	DVCL-153P-WH	1% - 100%
	Maestro C.L. dimmer, multi-location, CFL/LED/Incandescent	MACL-153MR-WH	1% - 100%
	Maestro Pro switch, Incandescent/Halogen/CFL/LED	MA-PRO-SW	1% - 100%
	Ariadni C.L. dimmer, CFL/LED/Incandescent, single pole	AYCL-153P-WH	1% - 100%
	Caseta Wireless dimmer, dimmable LED/CFL/Incandescent	PD-6WCL	1% - 100%
Leviton	Decora SureSlide dimmer, dimmable LED/CFL/Incandescent	6674-POW	1% - 100%
	Decora SureSlide dimmer, Incandescent/Halogen	6633-POW	1% - 100%
	IllumaTech dimmer, electronic low-voltage (ELV)	IPEO4-1LZ	5% - 100%
	IllumaTech dimmer, Incandescent	IPI06-1LZ	1% - 100%
	Decora SureSlide dimmer, dimmable LED/CFL/Incandescent slide-to-off	6672-1LW	1% - 100%
	Decora Digital dimmer, electronic low-voltage (ELV)/LED/CFL/Incandescent	DDE06-BLZ	1% - 100%
	Universal Rotary dimmer, Incandescent/LED/CFL	RNL06 -10Z	1% - 100%
	Universal Decora Rocker-Slide dimmer, Incandescent/LED/CFL	DSM10-1LZ	5% - 100%
	Decora Rocker-Slide dimmer, ELV/LED/CFL	DSE06-10Z	1% - 100%
	Rotary dimmer, Incandescent/LED/CFL	RDL06-10Z	5% - 100%
Cooper	Slide Dimmer for Incandescent/Fluorescent/LED/CFL/MLV/ELV	SAL06P	1% - 100%
Lutron	Diva dimmer, magnetic low-voltage (MLV), 3-way	DVLV-600P-WH	1% - 100%
	Skylark C.L. dimmer, CFL/LED/Incandescent, 3-way	SCL-153P-WH	1% - 100%

***NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross refrence that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.

amazon alexa | Google Assistant | Apple HomeKit | INSTEON | LUTRON | wemo

© ELCO Lighting 2026. All rights reserved • RV1 August 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

DIMMER COMPATIBILITY CHART

FOR REFERENCE ONLY

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

MANUFACTURER	PRODUCT	PART NUMBER	DIMMED LIGHT OUTPUT RANGE
0-10V - Triac/ELV Dimmers for ELK10DX			
Lutron	Diva 0-10V control for LED/fluorescent fixtures, single pole/3-way	DVSTV-WH	1% - 100%
Leviton	IllumaTech dimmer, 0-10V, LED power supplies	IP710-DOZ	1% - 100%
	Decora Slide dimmer, 0-10V, LED/fluorescent	DS710-10Z	1% - 100%

*NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross refrence that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.

amazon alexa | Google Assistant | Apple HomeKit | INSTEON | LUTRON | wemo

© ELCO Lighting 2026. All rights reserved • RV1 August 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

DIMMER COMPATIBILITY CHART

FOR REFERENCE ONLY

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

MANUFACTURER	PRODUCT	PART NUMBER	DIMMED LIGHT OUTPUT RANGE
120V - Triac/ELV Dimmers for ELK03, ELK07, ELK08, ELK09, ELK10, ELK11, and ELK13 Series			
Leviton	Decora SureSlide® Single Pole with Slide -to-Off	6672	15% - 100%
	Decora soft fade On/Off. Single Pole, 3-Way	1K35O2	5% - 100%
Lutron	Vive, 120V, 150W LED/CFL, 600W Incandescent/Halogen, FP, Single Pole/Multi-Location Dimmer, Commercial Application	MRF2S-6CL	12% - 91%
	Panel Model, Commercial/Residential Application, FP	GP (Harrier) Card	10% - 94%
	QS/Mailbox Power Module, 120/220 to 240V AC, LED/Incandescent/Halogen Load Type, Commercial/Residential Indoor Application, FP	LQRJ-WPM-6P	10% - 95%
	Grafik Eye 3000/HomeWorks, 120V, Incandescent/Fluorescent Load Type, Commercial/Residential Application, FP	HWI-WPM-6D-120	10% - 95%
	Panel Dimming Module, 120V, Commercial/Residential Application, FP	HW/LP-RPM-4U-120	10% - 95%
	Panel Adaptive Dimming Module, 120V, Commercial/Residential Application, FP	HW/LP-RPM-4A-120	9% - 95%
	HomeWorks® QS for CFL/LED, 120V, RP, Commercial/Residential Application	LQSE-4A1- DMQSE-4A1-D MQSE-3A1 MQSE-2A1-D	8% - 95%
	Energi Savr Node LED+ Phase Adaptive, Commercial Application, Reverse Phase, (Zone 1) (Zones 2-4)	QSN-4A5-S	8% - 95%
	Energi Savr Node LED+ Phase Adaptive, Commercial Application, Foward Phase, (Zone 1) (Zones 2-4)	QSN-4A5-S	10% - 97%
	RadioRA®2, 120V, 50/60-Hz, 150W LED or 600W Incandescent/Halogen, 3-Way & 4-Way, Residential Application	RRD-6CL	10% - 95%
	RadioRA®3, 120V, 250W LED/CFL or 500W Incandescent/Halogen, Single Pole, Multi-Location	RRST-PRO-N	10% - 95%
	HomeWorks® QS, 120V, 60-Hz, 150W LED/CFL or 600W Incandescent/Halogen/ MLV, Residential Application	HQRD-6CL(H2) HQRA-6CL(H2)	10% - 95%
	Homeworks QS, Residential Application, Reverse Phase	LQSE-4A-120-D	8% - 89%
	HomeWorks® for LED/Incandescent/Halogen loads, Reverse Phase, (Zone 1) (Zones 2-4)	LQSE-4A5-120-D	8% - 89%
	HomeWorks® for LED/Incandescent/Halogen loads, Foward Phase, (Zone 1) (Zones 2-4)	LQSE-4A5-120-D	10% - 100%
	Ariadni® C·L Single Pole/3-Way, 150W LED/CFL or 600W Incandescent/Halogen	AYCL-153P	10% - 100%
	Skylark Contour® C·L, Single Pole/3-Way, 150W LED/CFL or 600W Incandescent/ Halogen	CTCL-153P	10% - 100%
	Skylark® C·L Single Pole/3-Way, 150W LED/CFL or 600W Incandescent/Halogen	SCL-153P	10% - 100%
	Diva® Series 150W Single Pole/3-Way Dimmer	DVCL-153P	10% - 100%
	Skylark Contour® Single Pole/3-Way 1000W Incandescent/Halogen	CT-103P	10% - 100%

***NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross refrence that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.

amazon alexa | Google Assistant | Apple HomeKit | INSTEON | LUTRON | wemo

© ELCO Lighting 2026. All rights reserved • RV1 August 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

DIMMER COMPATIBILITY CHART

FOR REFERENCE ONLY

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

MANUFACTURER	PRODUCT	PART NUMBER	DIMMED LIGHT OUTPUT RANGE
120V - Triac/ELV Dimmers for ELK03, ELK07, ELK08, ELK09, ELK10, ELK11, and ELK13 Series			
Lutron	Skylark® Single Pole 300W ELV Preset Dimmer	SELV-300P	5% - 100%
	Skylark® Single Pole 600W Incandescent/Halogen, Slide-to-Off Dimmer	S-600P	5% - 100%
	Diva® 300W Single Pole/3-Way ELV Dimmer	DVELV-303P	10% - 100%
	Diva® 600W Single Pole Incandescent/Halogen Preset Dimmer	DV-600P	5% - 100%
	Ariadni® 600W Single Pole Magnetic Low Voltage Dimmer	AYLV-600P	5% - 100%
	Ariadni® 600W Single Pole/3-Way Incandescent/Halogen Dimmer	AY-603P	5% - 100%
	Maestro® 600W Single Pole/3-Way ELV Dimmer	MAELV-600	5% - 100%
	Maestro® C·L Single Pole/3-Way Dimmer. 150W Max for LED/CFL or 600W Max for Incandescent/Halogen	MACL-153M	10% - 100%
	Caséta® Wireless Dimmer	PD-6WCL	10% - 100%
SnapOne™ *MLV each transformer must be loaded to at least 50% of its maximum load	Control4® Centralized 8-Channel Adaptive Phase Dimmer, 120/277V AC, 50/60-Hz, 200W LED, 500W Fluorescent/CFL, 1000W Incandescent/Halogen/ELV/MLV*	C4-DIN-8APD	5% - 100%
	Control4® Centralized 8-Channel Forward Phase Dimmer, 100/120V AC, 50/60-Hz, 200W LED, 500W Fluorescent/CFL, 1000W Incandescent/Halogen/MLV*	C4-DIN-8FPD	25% - 100%
	Control4® Wireless Adaptive Phase Dimmer, 120V AC, 50/60-Hz, 120W LED, 300W Fluorescent/CFL, 600W Incandescent/Halogen	C4-APD120	23% - 100%
	Control4® Forward Phase Dimmer, 120V AC, 50/60-Hz, 200W LED, 500W Fluorescent/CFL, 1000W Incandescent/Halogen	C4-FPD120	4% - 100%
	Control4® Essential Forward Phase Dimmer, 120V AC, 60-Hz, 300W LED, 300W Fluorescent/CFL, 600W Incandescent/Halogen	C4-V-FPD120	1% - 100%

***NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross refrence that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.


amazon alexa | Google Assistant | Apple HomeKit | INSTEON | LUTRON | wemo

© ELCO Lighting 2026. All rights reserved • RV1 August 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

KOTO™ LED MODULE

PHOTOMETRIC REPORT

Product #: ELK0730
Wattage / Lumens: 10.6W / 813.8 lm
Luminaire LPW: 76.7 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	1186
5	1188
15	1004
25	536
35	254
45	93
55	27
65	12
75	6
85	3
90	1

ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4′	74.1	3.2′
6′	32.9	4.8′
8′	18.5	6.4′
10′	11.9	8.0′

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	580.1	71.3
0-40°	714.6	87.8
0-60°	797.0	98
0-90°	813.5	100

PHOTOMETRIC REPORT

Product #: ELK09SD
Wattage / Lumens: 10.9W / 605.1 lm
Luminaire LPW: 55.5 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	731
5	751
15	640
25	337
35	175
45	79
55	23
65	10
75	4
85	1
90	0

ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4′	45.7	3.1′
6′	20.3	4.7′
8′	11.4	6.2′
10′	7.31	7.8′

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	402.9	66.6
0-40°	510.3	84.4
0-60°	588.6	97.3
0-90°	601.9	99.5

PHOTOMETRIC REPORT

Product #: ELK1127
Wattage / Lumens: 12.5W / 1086.2 lm
Luminaire LPW: 86.9 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	1606
5	1542
15	1297
25	723
35	338
45	128
55	42
65	17
75	8
85	3
90	1

ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4′	100	3.2′
6′	44.6	4.8′
8′	25.1	6.4′
10′	16.1	7.9′

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	757.2	70.6
0-40°	933.9	87.1
0-60°	1,045.2	97.5
0-90°	1,066.1	99.4

PHOTOMETRIC REPORT

Product #: ELK1330
Wattage / Lumens: 11.8W / 1312.2 lm
Luminaire LPW: 111.2 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	1575
5	1497
15	1224
25	824
35	377
45	142
55	35
65	9
75	2
85	1
90	0

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4′	98.4	4.0′
6′	43.8	6.0′
8′	24.6	8.0′
10′	15.8	10.0′

ZONAL LUMEN SUMMARY


Zone	Lumens	%Luminaire
0-30°	879.8	67.1
0-40°	1,140.2	86.9
0-60°	1,298.7	99
0-90°	1,311.4	100

© ELCO Lighting 2026. All rights reserved • RV1 August 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

KOTO™ LED MODULE

PHOTOMETRIC REPORT

Product #: ELK08CT5 @3500K
Wattage / Lumens: 10.19W / 902.5 lm
Luminaire LPW: 88.5 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	1999
5	1840
15	1126
25	372
35	83
45	35
55	20
65	11
75	7
85	6
90	6

ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4′	124.9	2.6′
6′	55.5	3.8′
8′	31.2	5.1′
10′	20.0	6.4′

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	720.4	79.9
0-40°	786.4	87.2
0-60°	835.1	92.6
0-90°	860.9	95.4

PHOTOMETRIC REPORT

Product #: ELK0830-NSP
Wattage / Lumens: 10.5W / 871.4 lm
Luminaire LPW: 83.01 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	10979
5	4622
15	413
25	89
35	32
45	17
55	13
65	9
75	5
85	0
90	0

ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4′	686	0.8′
6′	305	1.2′
8′	172	1.6′
10′	110	2.0′

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	783.9	90.2
0-40°	809.4	93.2
0-60°	836.1	96.2
0-90°	852.2	98.1

PHOTOMETRIC REPORT

Product #: ELK10CT5 @4000K
Wattage / Lumens: 12.19W / 1043.6 lm
Luminaire LPW: 85.6 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	2348
5	2177
15	1349
25	455
35	101
45	41
55	22
65	12
75	7
85	5
90	5

ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4′	146.7	2.6′
6′	65.2	3.9′
8′	36.6	5.2′
10′	23.4	6.5′

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	849.4	81.4
0-40°	926.5	88.8
0-60°	981.4	94.1
0-90°	1,006.3	96.5

PHOTOMETRIC REPORT

Product #: ELK10CT5 @5000K
Wattage / Lumens: 12.3W / 1032.7 lm
Luminaire LPW: 83.9 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	2297
5	2078
15	1210
25	368
35	79
45	36
55	20
65	11
75	6
85	5
90	5

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4′	143.5	2.6′
6′	63.8	3.9′
8′	35.8	5.2′
10′	22.9	6.5′

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	837.9	81.2
0-40°	917.0	88.8
0-60°	971.5	94.1
0-90°	996.1	96.5

© ELCO Lighting 2026. All rights reserved • RV1 August 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.